

Adroit 605 which is ideal for underground transportation is designed to carry personnel and load at the same time. Level 2 certified FOPS - ROPS cabin is fully equipped with suspended seats, air conditioner and reversing audible and visitual warning system. It provides perfect mobility for the workers in underground mines and helps to carry the material up to 250 kg and 5 personnel. Adroit 605 has automatic transmission drive system which offers front wheel control, four wheel steering and crab steering.

GENERAL SPECIFICATIONS

- > Led control panel showing fault, warning and driving info
- > Front and rear parking sensor
- > Front and rear projectors
- > Cameras and recording system
- > Reversing audible and visual warning system
- > Eyebolts and towing hooks to use in loading and transporting the machine
- > 12 VDC output inside the cabin for vehicle radio
- > Fire extinguisher

DIMENSIONS AND WEIGHT

Length 5400 mmWidth 2150 mmWeight 4250 kg

OPERATOR CABIN

- > FOPS ROPS level 2 certified closed operator cabin
- > Air conditioner inside the cabin
- > Laminated and tempered glasses
- > Heated glasses and side-view mirrors
- > Washable cabin upholstery
- > 3 points contacted, non-slippery stairs
- > Emergency stop button inside the cabin
- > Operator seat
 - Suspended
 - Retractable seat belt
 - Sensor that activates the park brakes when the operator stand up

ENGINE

- Cummins ISF 2.8 110 kW@3200 rpm Diesel engine Euro Stage 3A
- > Engine / radiator fluid level warning

EXHAUST SYSTEM

> Catalytic converter with diesel particle filter

TRANSMISSION

- > Allison automatic transmission
- > 5 speed forward and 1 speed reverse
- > 4 wheel drive

AXLE SYSTEM

- > Planetary type Dana 211
- > Solid axle, coil spring suspension

TIRES

> 295 / 60 R22.5 size heavy duty tires, suitable for underground work

PERFORMANCE

- > Max. speed 40 km
- > Fully loaded max. speed in 15% incline : 20 km/h
- > Max. climb graident 50%

BRAKE SYSTEM

- > Service brake: Hydraulically powered two circuit oil immersed multidisc brake in both axles
- > Parking brake: S.A.H.R fail safe brake
- > Brake systems test set-up in cabin

STEERING

> Four wheel steering, crab steering, front wheel steering

FUEL SYSTEM

- > Tank capacity 80 L
- > Fuel hose securely fixed and isolated from the hot surfaces

HYDRAULIC SYSTEM

- > Tank capacity 30 L
- > Hydraulic filtration, fluid temperature and tank fluid level sensing and warning system


ELECTRICAL SYSTEM

- > Electrical components: IP65 and above protection grade
- > Battery 135 Ah
- > Led lighting lamps illuminating the movement direction
- > Flashing beacon lamps in amber colour
- > Fire resistant wiring


OPTIONAL COMPONENTS

- > EU Stage 5 diesel engine
- > Diesel engine fire suppression system





Climbing Capacity



Max. Speed - Max. Power of Climbing

Adroit 605 with 5-speed automatic transmission system offers long distance drives on flat terrains and have capacity of 50% gradient climbing.

Max. speed 40 km and fully loaded max. speed in 15% incline 20 km/h.

Turning Radius

